

Data Sheet

Open Steel Gratings - SP540-41/50-5

Forge Welded gratings are especially designed for platforms, landings and walkways for use in all types of industrial applications. Their specific features include, an excellent loading bearing capacity coupled with torsional rigidity, and are particular suited where heavy duty gratings are required. Corresponding welding between load bars and cross bars allows them to withstand shearing forces without any issues. Suitable depths and mesh patterns are specified based on using static and dynamic loading in conjunction with the required clear span.

Technical Details

Material	Mild Steel S275JR
Finish	Self Colour, Galvanised
Depth	40mm
Thickness	Load Bar (LB) 5mm
	Cross Bar (CB) 5 to 6mm (Diagonal)
Slip Resistance, Surface Type	PTV 41 (Wet), Plain
Mesh Pitch	41mm x 50mm,
Standard Stocked Sizes	6000mm x 1000mm (L x W)
Weight (per m ²)	42.5kg

Standard

BS EN 10025
BS EN ISO 1461
BS7976

Loading

Max Clear Span	1665mm	*Clear distance between supports
Uniform Distributed Load (UDL)	5kN/m ²	UDL to conform to **EN ISO 14122
UDL Deflection	3.70mm	Deflection for UDL load at given span
Point Load	1.5kN	Point Load to conform **EN ISO 14122
Contact Area	200 x 200mm	Point load area
Point Load Deflection	4.00mm	Deflection for Point load at given span
Fixing compatibility	B141K(S)	

*Supports must be fully supported on two opposing sides of the clear span

** EN ISO 14122 states deflection between adjacent loaded and unloaded panels must not exceed 4mm

*** Please note 41mm bearing bar pitch is non compliant with EN ISO 14122

Fixing Types

